

Berths and SPM Information

Jetties/SPM Specifications:

	BERTH-1	BERTH-2	BERTH-3	BERTH-4	BERTH-5	BERTH-6	SPM "A"	
Min. Water Depth Approaches @ CD	17.0 m	12.0 m	13.30 m	10.70 m	--	--	20.60 m	
Water Depth Alongside @ CD	18.0 m	14.0 m	12.30 m	11.90 m	14.90 m	13.70 m	26.0 m	
Max Draft Arrival @ CD	14.80 m	11.20 m	10.50 m	8.0 m	12.50 m	10.50 m	17.50 m	
Max Draft Sailing @ CD	15.50 m	11.90 m	11.0 m	8.50 m	13.0 m	11.50 m	17.50 m	
Minimum Displacement	---	---	---		6900 Tons		---	
Maximum Displacement	150,000 Tons	60,000 Tons	---		130,000 Tons		---	
Minimum DWT	5,000 Tons	3,000 Tons	2,000 Tons		5,000 Tons		35,000 Tons	
Maximum DWT	---	---	15,000 Tons		110,000 Tons		175,000 Tons	
Min LOA	120.0 m	74.0 m	---		74.0 m		---	
Max LOA	295.0 m	200.0 m	140.0 m	250 m	200 m	300 m		
Minimum Freeboard	0.30 m		1.40m		1.80 m		---	
Min. PBL (Fwd.)	30.0m	20.69m	14.50		18.125		NA	
Min PBL (Aft)	30.0m	20.69m	8.50		18.125		NA	
ML-Hose / MLA Sizes	Black Cargoes	02x12"	02x12"	01x08"	02x08"	01x16" & 01x12"	01x16" & 01x12"	01x16" Hose
	White Cargoes	02x16" & 01x12"	03x12"	01x08"	None	02x16"	02x16"	None

- Vessel is expected to arrange suitable reducer(s) based on the information above.

EXTERNAL LINES:

- 1 Line to Qidfah Power Plant (8")
- Port of Fujairah Matrix Manifold
- Port of Fujairah Tanker jetties
- Port of Fujairah VLCC Jetty (Crude & Fuel Oil)